

**CHARACTERISTICS**

Ambient temperature	-10 ÷ +90 °C
Fluid	50 µm filtered air, with or without lubrication
Commutation system	poppet
Max pressure	10 bar
Connections	M5, tube Ø4
Nominal bore (mm)	2,5
Nominal flow rate (NI/min)	70
Valve body	zamak
Seals	NBR
Spool	nickel-plated brass



**Mechanical operation for panel mounting**

■ Tube Ø4		■ M5	
	 AI-9500B 3/2 NC  AI-9510B 3/2 NO  AI-9520B 2/2 NC		 AI-9500BM 3/2 NC  AI-9510BM 3/2 NO  AI-9520BM 2/2 NC
	 AI-9550B 5/2  AI-9560B 5/3 o.c.  AI-9570B 5/3 p.c.		 AI-9550BM 5/2  AI-9560BM 5/3 o.c.  AI-9570BM 5/3 p.c.

o.c. = open centres    p.c. = pressurized centres

<b>Recessed button</b> AI-35B10N ■ AI-35B10R ■ AI-35B10V ■	<b>Protruding button</b> AI-35B11N ■ AI-35B11R ■ AI-35B11V ■	<b>Two-position head button</b> AI-35B13N ■ AI-35B13R ■	<b>Short lever selector</b> AI-35B20 2 steady positions AI-35B21 3 unsteady positions AI-35B22 3 steady positions	<b>Long lever selector</b> AI-35B25 2 steady positions AI-35B26 3 unsteady positions AI-35B27 3 steady positions	<b>Key selector</b> AI-35B30 2 steady positions AI-35B31 3 unsteady positions AI-35B32 3 steady positions