

TOLERANCE TUBE


TUBES Ø	Ø 5/32	Ø 5/16	Ø 1/4	Ø 3/8	Ø 1/2
TOLERANCES (INCH)	±0,003	±0,003	±0,003	± 0,005	± 0,005

INSERTION TUBE

DIAMETER TUBES Ø	Ø 5/32	Ø 5/16	Ø 1/4	Ø 3/8	Ø 1/2
TUBES INSERTION LENGHT (INCH)	0,551	0,688	0,629	0,728	0,846

OTRC-R


Male connector internal hexagonal BSPT thread nickel plated



CODE	ØD	T	ØP	A	L	CH	H
OTRC04R01	4	R1/8"	10	8	18,5	10	3
OTRC04R02	4	R1/4"	10	10	20	14	3
OTRC06R01	6	R1/8"	12	8	21	12	4
OTRC06R02	6	R1/4"	12	10	20	14	4
OTRC08R01	8	R1/8"	14	8	26	14	5
OTRC08R02	8	R1/4"	14	10	24	14	6
OTRC08R03	8	R3/8"	14	11	22	17	6
OTRC10R02	10	R1/4"	16	10	31	16	6
OTRC10R03	10	R3/8"	16	11	26	17	8
OTRC10R04	10	R1/2"	16	14	26,5	22	8
OTRC12R02	12	R1/4"	19	10	33	19	6
OTRC12R03	12	R3/8"	19	11	29,5	19	10
OTRC12R04	12	R1/2"	19	14	27	22	10

OTRC-G

Male connector internal hexagonal BSPP & metric thread nickel plated



CODE	ØD	T	ØC	ØP	A	L	CH	H
OTRC04M5	4	M5X0,8	7	10	4	19	9	2,5
OTRC04G01	4	G1/8"	14	10	5,5	18	10	3
OTRC04G02	4	G1/4"	16	10	6,5	18	10	3
OTRC06M5	6	M5X0,8	7	12	4	21	11	2,5
OTRC06G01	6	G1/8"	14	12	5,5	19,5	12	4
OTRC06G02	6	G1/4"	16	12	6,5	19,5	12	4
OTRC08G01	8	G1/8"	14	14	5,5	24,5	14	5
OTRC08G02	8	G1/4"	16	14	6,5	21,5	14	6
OTRC08G03	8	G3/8"	20	14	7,5	21,5	14	6
OTRC10G02	10	G1/4"	16	16	6,5	27,5	16	6
OTRC10G03	10	G3/8"	20	16	7,5	25	16	8
OTRC10G04	10	G1/2"	25	16	9	25	16	8
OTRC12G02	12	G1/4"	16	19	6,5	30	19	6
OTRC12G03	12	G3/8"	22	19	7,5	29,5	19	10
OTRC12G04	12	G1/2"	25	19	9	28	19	10

